



# LPVO-125

## *Vanishing Oil*

**PRODUCT DESCRIPTION:** LPVO-125 vanishing oil is specifically formulated for light duty applications in areas where a fast evaporation rate is necessary. LPVO-125 is non-staining and normally evaporates in less than 10 minutes leaving behind a thin dry-to-the-touch film. Once the carrier has evaporated, LPVO-125 will not bleed through wrappings, boxes, and most other packaging materials. The thin film left behind provides corrosion protection during transit and up to three months of indoor corrosion protection. LPVO-125 can be easily removed from the metal using a general purpose metal cleaner.

### PROPERTIES:

- Appearance: Brown Liquid
- Odor: Petroleum
- Density: 6.25 lbs/gal
- Flash Point: 125°F
- Film Thickness: 0.06 mils

### PRODUCT BENEFITS:

- Multi-metal compatibility
- Corrosion Protection – 60 days ASTM D-1748
- Dries Quickly
- Non-staining per Mil-C-22235

### USE PROCEDURE:

CONCENTRATION:	As Delivered
TEMPERATURE:	Ambient
PROCESS METHOD:	Light to medium duty stamping

**SAFETY:** Do Not Ingest. Product may be harmful if swallowed. Use with adequate ventilation. Do not leave container open when not in use. Do not store near open flame or in areas of excessive heat. Gloves and splash goggles should be worn when handling product. For full safety and first aid information consult SDS on this product prior to use.



2070 Calvin Avenue, SE  
Grand Rapids, MI 49507

(616) 245-9193  
[www.lilyproducts.com](http://www.lilyproducts.com)

The information contained in the bulletin is, to the best of our knowledge, true and accurate. All recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control, Lily Products of Michigan, Inc. disclaims any liability in connection with the use of the data or suggestions.